

APDU10351SW

! To be discontinued on: Sep 3, 2025



Overview

Lead time Usually in Stock	
----------------------------	--

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	5.9 ft (1.8 m)

Complementary

Input Voltage	208 V 3 phase	
Height	70.08 in (178.0 cm)	
Width	2.20 in (5.6 cm)	
Output Voltage	208 V	
Depth	2.95 in (7.5 cm)	
Net Weight	20.7 lb(US) (9.4 kg)	
Mounting Location	Side	
Mounting preference	No preference	
Input Plug Type	NEMA L21-30P	
Mounting Mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Communication Port Protocol	1000BASE-T 10/100BASE-T	
Line Rated Current	24 A	
Acceptable Input Voltage	200240 V	
Input current limits	30 A	
Load Capacity	8600 VA	
Input Frequency	50/60 Hz	
Outlet type and quantity	24 C13/C15/C19/C21 24C13/C15	

Environment

Product Certifications	TAA compliance	
	BAA compliance	
Standards	UL 62368-1	
	CSA C22.2 No 62368-1	
	FCC part 15 Subpart B	
IP Degree of Protection	IP44	
Ambient Air Temperature for Operation	23140 °F (-560 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (015240 m)	

Ordering and shipping details

GTIN	731304439806
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	77.95 in (198 cm)
Package 1 Width	4.57 in (11.6 cm)
Package 1 Length	8.19 in (20.8 cm)
Package 1 Weight	27.3 lb(US) (12.4 kg)

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	3781
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

4-in-1 outlet for increased flexibility



Multiple color options available





















