

# Product datasheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

APDU9953

### Overview

Lead time Usually in Stock

### Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Safety guide

### Complementary

Input Voltage	200...240 V
Height	1829 mm
Width	56 mm
Output Voltage	200...240 V
Depth	46 mm
Net weight	7.34 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Outlet type and quantity</b>	21 IEC 60320 C13 3 IEC 60320 C19
<b>Communication network type</b>	10/100/1000BASE-T

## Environment

<b>Product certifications</b>	VDE EAC RCM
<b>Standards</b>	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
<b>Ambient air temperature for operation</b>	-5...60 °C
<b>Relative humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-25...65 °C
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...15240 m

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	204 cm
<b>Package 1 Width</b>	12.4 cm
<b>Package 1 Length</b>	16.5 cm
<b>Package 1 Weight</b>	9.95 kg

## Contractual warranty

<b>Warranty (in months)</b>	36
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	2 909 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	55 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 848 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACH Regulation	<a href="#">REACH Declaration</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	71
End of life manual availability	<a href="#">End of Life Information</a>
Removable battery	Yes
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

