

APC IT POWER DISTRIBUTION MODULE 3 POLE 4 WIRE 60A IEC309 260CM

PDM3460IEC309-260

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead Time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Provided Equipment	Installation guide

Physical

Color	Black
Height	5.00 in (12.7 cm)
Width	17.52 in (44.5 cm)
Depth	15.98 in (40.6 cm)
Net Weight	8.62 lb(US) (3.91 kg)

Input

Input Frequency	60 Hz
Acceptable Input Voltage	200240 V
Max Line Current	60 A

Output

Maximum Total Current Draw Per Phase	60 A
Number Of Power Socket Outlets	1 IEC 309 60 A 3P+PE

Conformance

Product Certifications UL Listed

Ordering and shipping details

Gtin 731304272588

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	15.98 in (40.6 cm)
Package 1 Length	17.52 in (44.5 cm)
Package 1 Weight	9.81 lb(US) (4.45 kg)

Contractual warranty

Warranty 1 year repair or replace

Apr 22, 2024

Sustainability

Green Premium[™] label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >





Take-back Transparency

Resource performance



Take-Back Program Available

Well-being performance



Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information