Product data sheet

Specifications



APC NetShelter Rack PDU Advanced, Switched Metered Outlet, 3Phase, 17.3kW, 208V 60A, 42 Outlets, 460P9

APDU10452SM

Lead Time

Usually in Stock

Main

Color	Black
Product Or Component Type	PDU
Pdu Type	Switched metered outlet
Cord Length	5.91 ft (1.8 m)

Complementary

oompicilientary	
Input Voltage	208 V 3 phase
Height	70.08 in (178.0 cm)
Width	2.20 in (5.6 cm)
Output Voltage	208 V
Depth	2.95 in (7.5 cm)
Net Weight	24.91 lb(US) (11.3 kg)
Mounting Location	Side
Mounting Preference	No preference
Input Plug Type	IEC 60309 60 A 3P+PE
Mounting Mode	Rack-mounted
Rack Units	0U
Mounting Position	Vertical
Communication Port Protocol	1000BASE-T 10/100BASE-T
Line Rated Current	48 A
Acceptable Input Voltage	200240 V
Input Current Limits	60 A
Load Capacity	17300 VA
Input Frequency	50/60 Hz
Total Number Of Outlets	21 C13/C15/C19/C21 21C13/C15

Environment

Product Certifications

TAA compliance



Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B
Ip Degree Of Protection	IP44
Ambient Air Temperature For Operation	23140 °F (-560 °C)
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage Altitude	050000 ft (0.0015240.00 m)

Ordering and shipping details

Gtin

731304439882

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	77.95 in (198 cm)
Package 1 Width	5.20 in (13.2 cm)
Package 1 Length	10.31 in (26.2 cm)
Package 1 Weight	31.53 lb(US) (14.3 kg)

Contractual warranty

Warranty

3 years repair or replace

Apr 18, 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information

