

# Product data sheet

Specifications



APC Smart-UPS On-Line,  
2200VA, Rackmount 2U, 120V, 6x  
5-20R+1x L5-20R NEMA outlets,  
Network Card, Extended runtime,  
W/ rail kit

SRT2200RMXLA-NC

## Overview


Lead Time Usually in Stock

## Main

Main Input Voltage	120 V
Product Or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V
Kw Rating	1800 W
Rated Power In Va	2200 VA
Input Connection Type	NEMA 5-20P
Output Connection Type	6 NEMA 5-20R 1 NEMA L5-20R
Number Of Rack Unit	2U
Cable Length	6 ft (1.83 m)
Number Of Cables	1
Provided Equipment	CD with software Documentation CD Installation guide Network Management Card Rack mounting hardware Rack Mounting brackets Rack Mounting support rails USB cable Warranty card

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery Type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	0
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Voltage	72V
Battery Charge Power (Watts)	102 W rated
Battery Life	3...5 year(s)

Replacement Battery	<a href="#">APCRBC141</a> 
Extendable Run Time	1

## General

Topology	Double Conversion Online
Product Web Sub-Family	High density
Number Of Power Module	1400
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Color	Black
Height	3.35 in (8.5 cm)
Width	17.01 in (43.2 cm)
Depth	22.99 in (58.4 cm)
Net Weight	55.12 lb(US) (25 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes
Mounting Position	Horizontal

## Input

Input Frequency	40 - 70 Hz auto-sensing
-----------------	-------------------------

## Output

Maximum Configurable Power In Va	2200 VA
Max Configurable Power (Watts)	1800 W
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 2%
Crest Factor	3 : 1
Bypass Type	Built-in Bypass

## Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

## Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing

Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-4...122 °F (-20...50 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Acoustic Level	55 dBA
Heat Dissipation	535 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Free Slots	0
Pre-Installed Smartslot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (Epo)	Yes

## Surge Protection and Filtering

Surge Energy Rating	340 J
---------------------	-------

## Ordering and shipping details

Gtin	731304325154
Country Of Origin	PH

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	31.89 in (81 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	75.00 lb(US) (34.02 kg)

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

✓ Energy Efficient Product

---

✓ Take-Back Program Available

---

## Well-being performance

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

## Environmental Certifications

✓ Energy Star® [ENERGY STAR UPS V2.0 \(USA\)](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive [Compliant with Exemptions](#)

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---

California Proposition 65 [WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to \[www.P65Warnings.ca.gov\]\(http://www.P65Warnings.ca.gov\)](#)

---