

Product data sheet

Specifications



APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	330 W
Rated power in VA	600 VA
Input Connection Type	NEMA 5-15P
Output connection type	5 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	5 ft (1.52 m)
Battery Type	Lead-Acid battery
Provided equipment	User Manual

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	5.47 in (13.9 cm)
Width	10.79 in (27.4 cm)
Depth	4.13 in (10.5 cm)
Net Weight	7.69 lb(US) (3.49 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

Output

Max Configurable Power (Watts)	330 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	600 VA
Transfer Time	6ms typical : 10ms maximum


Conformance

Product Certifications	California (CEC) Battery Charger cTUVus NOM
Equipment protection policy	Lifetime : \$75000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...90 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	35 dBA
Heat dissipation	16 Btu/h

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	10 h
Battery Charge Power (Watts)	7 W rated
Battery power in VAH	78 VAh capacity 66 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	APCRBC154 
Extendable Run Time	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm LED status display with On Line : On Battery : Replace Battery and Overload indicators

Surge Protection and Filtering

Surge energy rating	490 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Let Through Voltage Rating	5 V

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304325116
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.72 in (19.6 cm)
Package 1 Width	6.61 in (16.8 cm)
Package 1 Length	14.29 in (36.3 cm)
Package 1 Weight	8.40 lb(US) (3.81 kg)
SCC14	10731304325113

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Recommended replacement(s)