



Product Highlights:

- **Compact 2-bay portable dock enables laptop-free backups and drive management via smartphone**
- **It pairs seamlessly with Lexar Professional Workflow SSDs and Readers to customize your workflow**
- **Equipped with USB Type-C™ delivering 10Gbps high-speed transfers, it ensures efficient data handling**
- **Includes a detachable 5000mAh battery for 4.5+ hours of backup**
- **Manage files via your phone, computer, or our app for a smoother experience**



Portable Post-Production Accelerator

The Lexar® Professional Workflow Go Docking Station is battery-powered to accelerate your post-production process in the field. You can quickly back up content on the go, no laptop required. Just use your smartphone to view content and manage the drive. The station features USB Type-C 10Gbps transfer speed for near-instant backup of large, high-res files and a thoughtful design that offers heat-dissipating, scratch-resistant aluminum housing to maintain maximum performance.

Compact, Portable 2-bay Docking Station. Compatible with Lexar Professional Workflow Portable SSDs and Readers so that you can customize to suit your needs, all in a design that's over 5x lighter than a laptop¹.

No Laptop Required. Back up on the go using your smartphone to view content and manage the drive. Plus, an additional USB-C port allows you to connect more devices.

Quickly Transfer High-Res Content. Features USB-C 10Gbps transfer speed for fast backup of large, high-res files.

More than 4.5 Hours of Battery Power. The included detachable, rechargeable 5000mAh battery pack provides more than 4.5 hours² of worry-free backup and can also charge other USB-C devices.

Durable Design. A durable aluminum body provides superior heat dissipation and scratch-resistance.

Rigorously Tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 28 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

¹ Compared to a 14" MacBook M3 Pro

² Based on internal testing, additional battery packs available for purchase

³ All modules are sold separately

⁴ Speeds based on internal testing on devices that support USB 3.2 Gen 2x2; performance may be lower depending on host device, interface, usage conditions, and other factors. Due to device limitations, the speed achievable on Workflow may not reach the maximum speed

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Lexar Retail SKU	Description	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LPWF600N-1ANGL	Lexar Professional Workflow Go, GL	Global	843367137541	10843367137548	10
LPWF730N-5ANGL	Lexar Professional Workflow CFexpress 4.0 Type A card reader		843367136179	10843367136176	
LPWF740N-6ANGL	Lexar Professional Workflow CFexpress 4.0 Type B card reader		843367136186	10843367136183	
LPWF720N-4ANGL	Lexar Professional Workflow Dual-Slot SD UHS-II Reader		843367136162	10843367136169	
LPWF710N-4ANGL	Lexar Professional Workflow SD/Micro SD UHS-II Reader		843367136155	10843367136152	
LPWF7502T-2ANGL	Lexar Professional Workflow Portable SSD 2TB		843367137350	10843367137357	
LPWF7504T-2ANGL	Lexar Professional Workflow Portable SSD 4TB		843367137367	10843367137364	
LPWF6B0N-NANGL	Lexar Professional Workflow Go Battery, GL		843367137558	10843367137555	

Specifications

Dimensions (L x W x H)	Workflow Go: 136 x 77 x 38mm Workflow Go battery: 77 x 38 x 36.8mm
Weight	Workflow Go: 318g Workflow Go battery: 156g
Battery Specification	Capacity: 5000mAh USB-C Input: 5V 3A, 9V 2.2A, 12V 1.67A USB-C Output: 5V 3A, 9V 2.2A, 12V 1.67A Total Output: 5V 3A Max
Warranty	Workflow Go and Workflow Go battery: 2-year

Compatible accessories specification

Interface	CFexpress 4.0 Type A Reader: USB 4 CFexpress 4.0 Type B Reader: USB 4 Dual-Slot SD Reader: USB 3.2 Gen 2 SD-MicroSD Reader: USB 3.2 Gen 2 Portable SSD: USB 3.2 Gen 2x2
Capacity (Portable SSD ³)	2TB 4TB
Speed (Portable SSD)	Sequential read speed up to 2000MB/s ⁴ Sequential write speed up to 2000MB/s ⁴
Operating Temperature	0° to 40°C (32°F to 104°F)
Storage Temperature	-20° to 85°C (-4°F to 185°F)

¹ Compared to a 14" MacBook M3 Pro

² Based on internal testing, additional battery packs available for purchase

³ All modules are sold separately

⁴ Speeds based on internal testing on devices that support USB 3.2 Gen 2x2; performance may be lower depending on host device, interface, usage conditions, and other factors. Due to device limitations, the speed achievable on Workflow may not reach the maximum speed

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Shock Resistance	1500G, duration 0.5ms, Half Sine Wave
Vibration Resistance	10~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis (X, Y, Z)
Dimensions (L x W x H)	CFexpress Type A Reader/CFexpress Type B Reader Dual-Slot SD Reader/SD-microSD Reader: 103.4 x 57.7 x 12.0mm
Weight	CFexpress Type A Reader: 84g CFexpress Type B Reader: 86.4g Dual-Slot SD Reader: 65.4g SD-microSD Reader: 60g Portable SSD: 145g
Warranty	CFexpress Type A Reader/CFexpress Type B Reader Dual-Slot SD Reader/SD-microSD Reader: 3-year Portable SSD: 5-year

¹ Compared to a 14" MacBook M3 Pro

² Based on internal testing, additional battery packs available for purchase

³ All modules are sold separately

⁴ Speeds based on internal testing on devices that support USB 3.2 Gen 2x2; performance may be lower depending on host device, interface, usage conditions, and other factors. Due to device limitations, the speed achievable on Workflow may not reach the maximum speed

Lexar is not liable for any loss of data or images.
Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.
Actual usable memory capacity may vary. 1GB equals 1 billion bytes.