Product data sheet

Specifications



APC Temperature & Humidity Sensor

AP9335TH

Lead time Usually in Stock Main Number of rack unit 0U Provided Equipment Humidity sensor Installation guide Temperature Sensor Humidity sensor Physical Color Black Keight 0.24 in (0.6 cm) Width 0.20 in (0.5 cm) Depth 0.20 in (0.5 cm) Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental 32131 "F (055 "C) Operating altitude 010000 ft Relative Humidity 095 % Ambient Air Temperature for Storage altitude 550000 tr (0.0015240.00 m) Storage Relative Humidity 095 %	Presentation	This Temperature & Humidity Sensor is a Universal sensor that monitors temperature and humidity ir your Data Center or Network Closet. IT has an RJ-45 connector. The cord length is 3.9m.
Number of rack unit OU Provided Equipment Humidity sensor Installation guide Temperature Sensor Physical Color Black Height 0.24 in (0.6 cm) Width 0.20 in (0.5 cm) Depth 0.20 in (0.5 cm) Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental 32131 °F (055 °C) Operating altitude 095 % Ambient Air Temperature for Storage S2149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Lead time	Usually in Stock
Provided Equipment Humidity sensor Installation guide Temperature Sensor Physical Color Black Height 0.24 in (0.6 cm) Width 0.20 in (0.5 cm) Depth 0.20 in (0.5 cm) Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental 32131 °F (055 °C) Operating altitude 095 % Ambient Air Temperature for Storage altitude 5149 °F (1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Main	
Installation guide Temperature Sensor Physical Color Black Height 0.24 in (0.6 cm) Width 0.20 in (0.5 cm) Depth 0.20 in (0.5 cm) Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental 32131 °F (055 °C) Operating altitude 01000 ft Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Number of rack unit	0U
ColorBlackHeight0.24 in (0.6 cm)Width0.20 in (0.5 cm)Depth0.20 in (0.5 cm)Net Weight0.40 lb(US) (0.18 kg)Mounting preferenceNo preferenceMounting ModeRack-mountedEnvironmental32131 °F (055 °C)Operation01000 ftRelative Humidity095 %Ambient Air Temperature for Storage5149 °F (-1565 °C)Storage altitude05000 ft (0.0015240.00 m)	Provided Equipment	Installation guide
Height 0.24 in (0.6 cm) Width 0.20 in (0.5 cm) Depth 0.20 in (0.5 cm) Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental 32131 °F (055 °C) Operating altitude 010000 ft Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Physical	
Width0.20 in (0.5 cm)Depth0.20 in (0.5 cm)Net Weight0.40 lb(US) (0.18 kg)Mounting preferenceNo preferenceMounting ModeRack-mountedEnvironmental32131 °F (055 °C)Operation32131 °F (055 °C)Operating altitude010000 ftRelative Humidity095 %Ambient Air Temperature for Storage5149 °F (-1565 °C)Storage altitude050000 ft (0.0015240.00 m)	Color	Black
Depth0.20 in (0.5 cm)Net Weight0.40 lb(US) (0.18 kg)Mounting preferenceNo preferenceMounting ModeRack-mountedEnvironmental32131 °F (055 °C)Operation32131 °F (055 °C)Operating altitude010000 ftRelative Humidity095 %Ambient Air Temperature for Storage5149 °F (-1565 °C)Storage altitude050000 ft (0.0015240.00 m)	Height	0.24 in (0.6 cm)
Net Weight 0.40 lb(US) (0.18 kg) Mounting preference No preference Mounting Mode Rack-mounted Environmental	Width	0.20 in (0.5 cm)
Mounting preferenceNo preferenceMounting ModeRack-mountedEnvironmental32131 °F (055 °C)Operation32131 °F (055 °C)Operating altitude010000 ftRelative Humidity095 %Ambient Air Temperature for Storage altitude5149 °F (-1565 °C)Storage altitude050000 ft (0.0015240.00 m)	Depth	0.20 in (0.5 cm)
Mounting Mode Rack-mounted Environmental Ambient Air Temperature for Operation 32131 °F (055 °C) Operating altitude 010000 ft Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C)	Net Weight	0.40 lb(US) (0.18 kg)
Environmental Ambient Air Temperature for Operation 32131 °F (055 °C) Operating altitude 010000 ft Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Mounting preference	No preference
Ambient Air Temperature for Operation32131 °F (055 °C)Operating altitude010000 ftRelative Humidity095 %Ambient Air Temperature for Storage5149 °F (-1565 °C)Storage altitude050000 ft (0.0015240.00 m)	Mounting Mode	Rack-mounted
Operation 010000 ft Operating altitude 010000 ft Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Environmental	
Relative Humidity 095 % Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)		32131 °F (055 °C)
Ambient Air Temperature for Storage 5149 °F (-1565 °C) Storage altitude 050000 ft (0.0015240.00 m)	Operating altitude	010000 ft
Storage 050000 ft (0.0015240.00 m)	Relative Humidity	095 %
		5149 °F (-1565 °C)
Storage Relative Humidity 095 %	Storage altitude	050000 ft (0.0015240.00 m)
	Storage Relative Humidity	095 %
Ordering and shipping details	Category	09305 - INDUSTRIAL UPS

<u> </u>	
Category	09305 - INDUSTRIAL UPS
GTIN	731304234005
Returnability	No



Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.39 in (1 cm)
Package 1 Width	10.00 in (25.4 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	0.62 lb(US) (0.279 kg)

Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty

2 years repair or replace

Recommended replacement(s)