

# Product data sheet

Specifications



## Rack PDU, Metered, 2U, 30A, 208V, (12) C13s & (4) C19



AP7811B

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	200 V 208 V 230 V
PDU Type	Metered
Main Output Voltage	208 V
Input Connection Type	NEMA L6-30P
Number of rack unit	2U
Cable length	12 ft (3.66 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual

### Physical

Height	3.46 in (8.8 cm)
Width	17.48 in (44.4 cm)
Depth	4.41 in (11.2 cm)
Net Weight	7.41 lb(US) (3.36 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

### Input

Line Rated Current	24 A
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz

## Output

Number of power socket outlets	12 IEC 60320 C13 4 IEC 60320 C19
--------------------------------	-------------------------------------

## Conformance

Product Certifications	cUL Listed CSA PSE UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950

## Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

GTIN	731304331490
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.51 in (14 cm)
Package 1 Width	14.49 in (36.8 cm)
Package 1 Length	20.00 in (50.8 cm)
Package 1 Weight	11.95 lb(US) (5.42 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

**Recommended replacement(s)**