

# Product data sheet

Specifications



## Rack PDU 2G, Switched, 30A, 200/208V, (21) C13 & (3) C19 (BEING DISCONTINUED - SEE APDU9941)

AP8941

⚠ Discontinued

⚠ Discontinued on: 20 June 2022

⚠ End-of-service on: 09 November 2022

### Overview

#### Presentation

APC Switched Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Individual outlet control provides advanced load management. Real-time remote monitoring and user-defined alarms help prevent potential circuit overloads that can cause accidental power loss to critical equipment. Included capabilities include individual remote on/off by outlet, power-on sequencing with time delays, outlet level grouping, and outlet grouping on multiple APC Switched Rack PDUs. Easily access, configure, and manage this metered PDU from remote locations. A network management interface provides standards-based management via Web, SNMP, and Command Line Interface. This Switched PDU from APC provides (21) IEC 60320 C13, (3) IEC 60320 C190 outlets to supply power to rack equipment. User customized alarms and an embedded memory log are included. Volts, amps, real power (kW), and energy (kWh) data is provided to support energy management. An embedded log memory to reports historic metered data. Display details current, power, and voltage measurements and offers local user access. An environmental monitoring port for external temperature/humidity monitoring is available (sensor sold separately model AP9335T or AP9335TH). Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events and breakers are ultra-low profile. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable.

#### Lead time

Usually in Stock

### Main

#### Main Input Voltage

200 V  
208 V  
230 V

#### PDU Type

Switched

#### Main Output Voltage

200 V  
208 V

#### Input Connection Type

NEMA L6-30P

#### Number of rack unit

0U

#### Cable length

10 ft (3.05 m)

#### Number of cables

1

#### Provided Equipment

Installation guide  
Rack Mounting brackets  
Serial configuration cable  
Safety guide

### Physical

#### Color

Black

#### Height

72.01 in (182.9 cm)

#### Width

2.20 in (5.6 cm)

Depth	1.81 in (4.6 cm)
Net Weight	16.84 lb(US) (7.64 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Not rack-mountable
USB compatible	No

## Input

Line Rated Current	24 A
Max line current	30 A
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz

## Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

## Conformance

Product Certifications	cUL Listed PSE UL Listed VCCI Class A
Standards	FCC Part 15 class A ICES-003

## Environmental

Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304277088
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.31 in (204 cm)
Package 1 Width	4.88 in (12.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	22.05 lb(US) (10 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)

AP8941 is replaced by:



1x

APC Rack PDU, 9000 switched, 0U, 30A, 200V and 208V, 21 C13 and C15, 3 C19 and C21 sockets  
APDU9941