Mitsubishi Professional Discs for XDCAM

Mitsubishi Professional Discs for XDCAM are manufactured in Japan at Mitsubishi Chemical Media factories for distribution by Verbatim Americas LLC. Verbatim, a subsidiary of Mitsubishi Chemical Media, is the worldwide leader in optical media and has a long history of quality and reliability.

Verified by Sony to ensure performance and compatibility with XDCAM equipment, Mitsubishi Re-Writable Professional Discs are available in 23GB and 50GB capacities, providing up to 122 minutes of HD recording time on a single disc.* Professional Discs utilize blue-violet laser technology for extremely high-density recording, and allow for instant

random access to previously recorded materials.

A rugged protective cartridge makes these discs extremely durable, resistant to dirt, dust, fingerprints as well as vibration and shock. The discs are packed in a semi-transparent case and include a paper insert to aid in the organization of recorded materials.

Mitsubishi Professional Discs allow for up to 1,000 recording cycles and 1,000,000 read cycles without signal degradation. Combined with a 50-year archival and shelf life, these discs are a perfect archival solution for HD video or other important data. All Mitsubishi Professional Disc products are backed by Verbatim's Limited Lifetime Warranty.



FEATURES & BENEFITS

- Manufactured in Japan at Mitsubishi Chemical Media factories officially licensed by Sony for the production of Professional Disc products
- Discs are officially verified by Sony for use with XDCAM equipment
- Up to 122 minutes of HD recording time*
- 23GB and dual-layer 50GB capacities available
- Rugged protective cartridge
- Pre-formatted for use with XDCAM products
- 50 year archival life
- Up to 1,000 recording cycles and 1,000,000 read cycles without loss of signal
- Limited Lifetime Warranty

*23GB - 43 minutes, 50GB - 122 minutes. Recording times based on MPEG HD 422 50MBps

HARDWARE COMPATIBILITY

| CAMCORDER | | | | | | | | |
|-----------|-----------|----------|----------|---------|---------|----------|--|--|
| PDW-850 | PDW-F800 | PDW-750 | PDW-740 | PDW-700 | PDW-680 | PDW-F355 | | |
| PDW-F335 | PDW-F350L | PDW-F330 | PDW-539P | PDW-510 | PDW-530 | | | |

For full compatibility information, please visit www.verbatim.com/professional-disc/compatibility.

RECORD TIMES

| | RECORDING FORMAT | RECORDING BIT RATE | PFD23A/3 | PFD50DLA/3 | PFD100TLA | PFD128QLW |
|---------------------|---------------------|-----------------------|----------|------------|-----------|-----------|
| High Definition | XDCAM MPEG HD422 | 50 Mbps | 43 min. | 95 min. | 190 min. | 240 min. |
| | | 35 Mbps | 65 min. | 145 min. | 290 min. | 360 min. |
| | XDCAM HD | 25 Mbps | 85 min. | 190 min. | 380 min. | 480 min. |
| | | 18 Mbps | 112 min. | 248 min. | 496 min. | 600 min. |
| Standard Definition | MPEG IMX | 50 Mbps | 45 min. | 100 min. | 200 min. | 240 min. |
| | | 40 Mbps | 55 min. | 120 min. | 240 min. | 300 min. |
| | DVCAM | 30 Mbps | 68 min. | 150 min. | 300 min. | 360 min. |
| | | 25 Mbps | 85 min. | 185 min. | 370 min. | 450 min. |

SPECIFICATIONS

| | 98927 | 98928** | | | | |
|-------------------------|---------------------------|-----------------------------|--|--|--|--|
| Case Shape | Standard | Standard | | | | |
| Disc Type | Rewritable | Rewritable | | | | |
| Formatted capacity | 23.3GB*** | 50GB*** | | | | |
| Recording Format | Phase Change Recording | Phase Change Recording | | | | |
| Laser Wavelength | 405 nm | 405 nm | | | | |
| Cartridge Dimensions | 128.6 x 130.6 x 9.1 mm ** | 128.6 x 130.6 x 9.1 mm **** | | | | |
| Disc Diameter | 120 mm**** | 120 mm**** | | | | |
| Disc Thickness | 1.2 mm | 1.2 mm | | | | |
| Cover Layer Thickness | 0.1 mm | 0.1 mm | | | | |
| Max Data Transfer Rate | 86 Mbps | 86 Mbps | | | | |
| Substrate | Polycarbonate | Polycarbonate | | | | |
| Erase/Write/Read cycles | More than 1,000 time | More than 1,000 time | | | | |
| Read Stability | More than 1,000,000 | More than 1,000,000 | | | | |
| Operating Conditions | -5~55 degC/3~90%RH | -5~55 degC / 3~90%RH | | | | |
| Storage Conditions | -10~55 degC / 3~90%RH | -10~55 degC / 3~90%RH | | | | |
| Estimated shelf life | More than 50 years | More than 50 years | | | | |
| Estimated archival life | More than 50 years | More than 50 years | | | | |

^{** 98928} can be used with XDCAM® equipment which is compatible with dual layer discs.

*** Since a portion of data area will be used for data management, the available capacity may vary.

**** Nominal value.