

<b>Availability</b>	<b>64GB-512GB—Q4 2019</b>
<b>Brand</b>	Lexar
<b>Product Name Full</b>	Lexar® Professional CFexpress™ Type B card
<b>Product Name Short</b>	Professional CFexpress™ Type B
<b>Product Line</b>	Professional
<b>Marketing Text Long 25-Word Description (&lt;750characters)</b>	Get rugged durability and the powerful performance you need to capture high-quality images and seamless RAW 4K video with read transfer speeds of up to 1750MB/s <sup>1</sup> .
<b>Marketing Text 50-Word Description (&lt;750characters)</b>	Capture high-quality images and seamless RAW 4K video with the Lexar® Professional CFexpress™ Type B card. Designed to leverage the capabilities of next generation cinema cameras and DSLRs, this rugged card supports both PCI Express® Gen 3 and NVMe protocol while providing high-speed performance, durability, and reliability, with a read transfer speed of up to 1750MB/s <sup>1</sup> .
<b>Marketing Text 100-Word Description (&lt;750characters)</b>	<b>Capture high-quality images and HD video with professional-level speeds and capacities</b> Capture high-quality images and seamless RAW 4K video with Lexar® Professional CFexpress™ Type B card. Designed to leverage the capabilities of the next generation cinema cameras and DSLRs, this rugged card supports both PCI Express® Gen 3 and NVMe protocol while providing high-speed performance, durability, and reliability, with a read transfer speed of up to 1750MB/s <sup>1</sup> . This improves transfer speed from card to computer, dramatically accelerating workflow. Available in capacities from 64GB to 512GB, the Lexar Professional CFexpress Type B cards come backed by expert technical support and a limited lifetime warranty.
<b>Bullet Feature 1</b>	Superior performance with transfer speeds of up to 1750MB/s <sup>1</sup> read
<b>Bullet Feature 2</b>	Shoot more high-quality images and RAW 4K video
<b>Bullet Feature 3</b>	Backwards compatible with select XQD® cameras <sup>2</sup>
<b>Bullet Feature 4</b>	Utilizes PCIe® 3.0 and NVMe™ protocol for unmatched speeds
<b>Bullet Feature 5</b>	Write speeds of up to 1000MB/s
<b>Bullet Feature 6</b>	Limited lifetime warranty
<b>Footnote(s)/ Disclaimer(s)</b>	<p>Warning: CFexpress Type B cards are only compatible with devices that support the CFexpress format. Highest transfer speed achieved only when used with an CFexpress Type B reader, indicated by a boxed USB logo on the product. Contact your device manufacturer for details.</p> <p><sup>1</sup>Up to 1750MB/s read transfer, write speeds lower. Speeds based on internal testing. Actual sustained speed may vary depending on host device.</p> <p><sup>2</sup>Compatible with firmware enabled CFexpress™ cameras</p> <p>Lexar is not liable for any loss of data or images.</p> <p>[Note:] [Product page only:] Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.</p>

	Actual usable memory capacity may vary. 1GB equals 1 billion bytes.  Limited lifetime warranty is limited to 10 years from purchase in Germany and regions not recognizing lifetime warranty.
<b>Warranty</b>	Limited lifetime warranty
<b>Market Segment</b>	Electronics, computers & accessories, cameras & photo, video
<b>Category</b>	Digital camera accessories, video camera accessories, DSLR, CFexpress
<b>Sub Category</b>	CFexpress™, Lexar
<b>Keywords for Search</b>	CFexpress memory card, CFexpress Type B, CFexpress, CFexpress Type B card, CFexpress flash memory, memory cards, flash cards, CFexpress memory, memory cards digital camera, digital camera cards, lexar professional, USB 3.1 reader, CFexpress reader

Specifications	
<b>Module Type/ Form Factor</b>	CFexpress Type B
<b>Capacities and Speed</b>	64GB, 128GB, 256GB, 512GB —Up to 1750MB/s read, up to 1000MB/s write
<b>Operating Temperature</b>	-10° C to 70° C (14°F to 158°F)
<b>Storage Temperature</b>	-40° C to 85° C (-40°F to 185°F)
<b>Shock</b>	1500G, duration 0.5ms, Half Sine Wave
<b>Vibration</b>	10~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis(X,Y,Z)
<b>Humidity</b>	5% to 95%, non-condensing

Ordering information				
<b>Single and/or Master Carton UPC (NA)</b>	<b>Part Number</b>	<b>Description</b>	<b>Single UPC</b>	<b>10 Pack UPC</b>
	LCFX10-64GCRBNA	Lexar CFExpress Professional 64GB RB, NA	843367119943	10843367119940
	LCFX10-128CRBNA	Lexar Pro CFExpress Professional 128GB RB NA	843367104864	10843367104861
	LCFX10-256CRBNA	Lexar Pro CFExpress Professional 256GB RB NA	843367104888	10843367104885
	LCFX10-512CRBNA	Lexar Pro CFExpress Professional 512GB RB NA	843367104901	10843367104908

<b>Single and/or Master Carton UPC (GLOBAL)</b>	<b>Part Number</b>	<b>Description</b>	<b>Single UPC</b>	<b>10 Pack UPC</b>
	LCFX10-64GCRB	Lexar CFExpress Professional 64GB RB, Global	843367119967	10843367119964
	LCFX10-128CRB	Lexar Pro CFExpress Professional 128GB RB Global	843367104925	10843367104922
	LCFX10-256CRB	Lexar Pro CFExpress Professional 256GB RB Global	843367104949	10843367104946
	LCFX10-512CRB	Lexar Pro CFExpress Professional 512GB RB Global	843367104963	10843367104960
<b>Country of Origin</b>	China			
<b>Harmonized Tariff Schedule</b>	8471.60.9050			
<b>Compliance</b>	Recycle, WEEE, FCC, CE, C-Tick, VCCI, Two Japanese Recycle			

<b>Weights and Dimensions</b>		
<b>Unit Weight</b>	0.017 lbs	7.80 g
<b>Unit Dimensions L x W x H</b>	1.515" L x 1.165" W x 0.149" H	38.50mm L x 29.60mm W x 3.80mm H
<b>Image</b>		
<b>Retail Box (All Regions)</b>		
<b>Package Type</b>	Retail Box	
<b>Qty Per Package</b>	1	
<b>Shipping Weight</b>	0.09 lbs	40 g

<b>Package Dimensions W x H x D</b>	3.9062" L x 0.5118" W x 4.7445" H	99.2mm L x 13mm W x 120.5mm H
<b>Retail Box (All Regions)</b>		
<b>Package Type</b>	Retail Box	
<b>Retail Master Pack Quantity</b>	10	
<b>Shipping Weight</b>	1.0141 lbs	0.46kg
<b>Package Dimensions L x W x D</b>	5.905" L x 5.905" W x 4.527" D	150mm L x 150 mm W x 115mm D