



# APC Essential SurgeArrest 6 Outlet Wall Mount With USB, 120V

P6WU2

#### Overview

Lead time Usually in Stock

#### Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Provided equipment	User Manual

# **Physical**

Color	Beige
Height	4.02 in (10.2 cm)
Width	1.50 in (3.8 cm)
Depth	5.51 in (14 cm)
Net Weight	0.55 lb(US) (0.25 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

## Input

Input power	1200 W
Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

### **Output**

Number of power socket outlets	6
Outlet standard	NEMA 5-15R

#### **Conformance**

**UL 1449 TVSS Rating** 400

Equipment protection policy	Lifetime: \$50000
Environmental	
Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %

# **Surge Protection and Filtering**

**Product Certifications** 

ETL

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	72 kA common mode 60 kA per phase normal mode
Surge energy rating	1080 J

0...50000 ft (0.00...15240.00 m)

# Ordering and shipping details

# **Packing Units**

Storage altitude

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.49 in (24.1 cm)
Package 1 Width	7.76 in (19.7 cm)
Package 1 Length	2.24 in (5.7 cm)
Package 1 Weight	0.57 lb(US) (0.26 kg)
Number of Units in Package 2	6
Package 2 Height	10 in (254.00 mm)
Package 2 Width	8.4 in (213.36 mm)
Package 2 Length	13.4 in (340.36 mm)
Package 2 Weight	5 lb(US) (2.27 kg)
Number of Units in Package 3	504
SCC14	10731304331824

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant FURNHS Declaration

Mar 8, 2023

Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Contractual warranty	
Warranty	Limited Lifetime

Recommended replacement(s)