Product data sheet

Specifications





APC Essential SurgeArrest 6 Outlet 10 Foot Cord 120V

PE610

О				

Lead time Usually in Stock

Main

IVIAIII	
Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	10 ft (3.05 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black Gray
Height	11.02 in (28 cm)
Width	2.05 in (5.2 cm)
Depth	1.18 in (3 cm)
Net Weight	1.48 lb(US) (0.67 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	6
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS Rating	500
Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 % Non-condensing
Storage altitude	050000 ft (0.0015240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	48 kA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

GTIN 731304336600

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	12.20 in (31 cm)
Package 1 Width	1.57 in (4 cm)
Package 1 Length	5.71 in (14.5 cm)
Package 1 Weight	1.70 lb(US) (0.77 kg)
Number of Units in Package 2	6
Package 2 Height	13.58 in (344.93 mm)
Package 2 Width	6.42 in (163.07 mm)
Package 2 Length	10.71 in (272.03 mm)
Package 2 Weight	10.85 lb(US) (4.92 kg)
Number of Units in Package 3	264
SCC14	10731304336607

Offer Sustainability

Sustainable offer status Green Premium product

California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Contractual warranty	
Warranty	Limited Lifetime

Recommended replacement(s)