

Product data sheet

Specifications



APC Essential SurgeArrest 6 Outlet 25 Foot Cord 120V

PE625

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 25 ft (7.62 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Gray
Height 11.02 in (28 cm)
Width 2.05 in (5.2 cm)
Depth 1.18 in (3 cm)
Net Weight 2.98 lb(US) (1.35 kg)
Mounting preference No preference
Mounting Mode Rack-mounted

Input

Maximum Line Current per phase 15 A
Input Frequency 50/60 Hz
Maximum Input Current per Phase 15 A
Switching current capacity 15 A

Output

Number of power socket outlets 6
Outlet standard NEMA 5-15R

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

UL 1449 TVSS Rating	500
Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	48 kA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

GTIN	731304337027
------	--------------

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	12.20 in (31 cm)
Package 1 Width	1.77 in (4.5 cm)
Package 1 Length	10.04 in (25.5 cm)
Package 1 Weight	3.31 lb(US) (1.5 kg)
Number of Units in Package 2	6
Package 2 Height	13.58 in (344.93 mm)
Package 2 Width	10.75 in (273.05 mm)
Package 2 Length	11.89 in (302.01 mm)
Package 2 Weight	20.81 lb(US) (9.44 kg)
Number of Units in Package 3	432
SCC14	10731304337024

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
-----------------	------------------

Recommended replacement(s)