

Product data sheet

Specifications



APC Essential SurgeArrest PE76, 7 Outlets, 6 Foot Cord, 120V

PE76

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Gray
Height 1.18 in (3 cm)
Width 2.05 in (5.2 cm)
Depth 13.70 in (34.8 cm)
Net Weight 1.21 lb(US) (0.55 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Maximum Line Current per phase 15 A
Input Frequency 50/60 Hz
Maximum Input Current per Phase 15 A
Switching current capacity 15 A

Output

Number of power socket outlets 7
Outlet standard NEMA 5-15R

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	1440 J

Ordering and shipping details

GTIN	731304328957
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4 cm)
Package 1 Width	14.96 in (38 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	1.43 lb(US) (0.65 kg)
Number of Units in Package 2	6
Package 2 Height	10 in (254.00 mm)
Package 2 Width	6 in (152.40 mm)
Package 2 Length	16 in (406.40 mm)
Package 2 Weight	9.48 lb(US) (4.30 kg)
Number of Units in Package 3	360
SCC14	10731304328954

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
-----------------	------------------

Recommended replacement(s)