

Product data sheet

Specifications



APC Home Office SurgeArrest 12 Outlets, 120V

PH12

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Height 1.18 in (3 cm)
Width 3.03 in (7.7 cm)
Depth 12.09 in (30.7 cm)
Net Weight 1.48 lb(US) (0.67 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Maximum Line Current per phase 15 A
Input Frequency 50/60 Hz
Maximum Input Current per Phase 15 A
Switching current capacity 15 A

Output

Number of power socket outlets 12
Outlet standard NEMA 5-15R

Conformance

Product Certifications MET USA

Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN	8411314066804
-------------	---------------

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	13.19 in (33.5 cm)
Package 1 Length	5.71 in (14.5 cm)
Package 1 Weight	1.70 lb(US) (0.77 kg)
Number of Units in Package 2	6
Package 2 Height	12.6 in (320.04 mm)
Package 2 Width	6.3 in (160.02 mm)
Package 2 Length	13.78 in (350.01 mm)
Package 2 Weight	11.04 lb(US) (5.01 kg)
Number of Units in Package 3	324
SCC14	10731304335945

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration

Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	Lifetime
-----------------	----------

Recommended replacement(s)