

Product data sheet

Specifications



APC Home Office SurgeArrest 8 Outlets, 120V

PH8

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Height 1.18 in (3 cm)
Width 3.03 in (7.7 cm)
Depth 9.72 in (24.7 cm)
Net Weight 1.32 lb(US) (0.6 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Maximum Line Current per phase 15 A
Input Frequency 50/60 Hz
Maximum Input Current per Phase 15 A
Switching current capacity 15 A

Output

Number of power socket outlets 8
Outlet standard NEMA 5-15R

Conformance

Product Certifications MET Canada

MET USA

Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN	731304335979
-------------	--------------

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	11.22 in (28.5 cm)
Package 1 Length	5.71 in (14.5 cm)
Package 1 Weight	1.54 lb(US) (0.7 kg)
Number of Units in Package 2	6
Package 2 Height	12.6 in (320.04 mm)
Package 2 Width	6.3 in (160.02 mm)
Package 2 Length	11.81 in (299.97 mm)
Package 2 Weight	10.08 lb(US) (4.57 kg)
Number of Units in Package 3	432
SCC14	10731304335976

Contractual warranty

Warranty	Limited Lifetime
-----------------	------------------

Recommended replacement(s)