

Product data sheet

Specifications



APC Performance SurgeArrest 10 Outlet with 2 Port 2.4A USB Charger 120V

P10U2

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Height 11.26 in (28.6 cm)
Width 5.00 in (12.7 cm)
Depth 1.26 in (3.2 cm)
Net Weight 1.83 lb(US) (0.83 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Input Frequency 50/60 Hz
Switching current capacity 15 A

Output

Number of power socket outlets 10
Outlet standard NEMA 5-15R

Conformance

UL 1449 TVSS Rating L-N: 400
L-G: 500
N-G: 500

Product Certifications cULus

Standards FCC Part 15 class B

UL 1310
UL 1363
UL 1449

Equipment protection policy Lifetime : \$300000

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	75 dB
Peak current	56 kA common mode 196 kA normal mode
Surge energy rating	4320 J

Ordering and shipping details

GTIN 731304336556

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	13.19 in (33.5 cm)
Package 1 Width	1.69 in (4.3 cm)
Package 1 Length	7.87 in (20 cm)
Package 1 Weight	2.09 lb(US) (0.95 kg)
Number of Units in Package 2	6
Package 2 Height	8.98 in (228.09 mm)
Package 2 Width	11.42 in (290.07 mm)
Package 2 Length	14.17 in (359.92 mm)
Package 2 Weight	13.89 lb(US) (6.30 kg)
Number of Units in Package 3	216
SCC14	10731304336553

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
----------	------------------

Recommended replacement(s)