

# Product data sheet

Specifications



## APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V

P11VNT3

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 120 V

Input Connection Type NEMA 5-15P

Cable length 8 ft (2.44 m)

Number of cables 1

Provided equipment  
6ft Network cable  
Coaxial cable  
Cord management straps  
Telephone Cable  
User Manual

### Physical

Color Black

Height 1.57 in (4 cm)

Width 4.69 in (11.9 cm)

Depth 11.89 in (30.2 cm)

Net Weight 2.34 lb(US) (1.06 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

### Input

Input Frequency 50/60 Hz

Switching current capacity 15 A

### Output

Number of power socket outlets 11

Outlet standard NEMA 5-15R

### Conformance

UL 1449 TVSS Rating  
L-N: 400  
L-G: 500  
N-G: 500

|                             |                     |
|-----------------------------|---------------------|
| Product Certifications      | CSA<br>NOM          |
| Standards                   | UL 1363<br>UL 1449  |
| Equipment protection policy | Lifetime : \$100000 |

## Environmental

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 32...113 °F (0...45 °C)          |
| Relative Humidity                     | 0...95 %                         |
| Operating altitude                    | 0...10000 ft                     |
| Ambient Air Temperature for Storage   | 5...113 °F (-15...45 °C)         |
| Storage Relative Humidity             | 0...95 %                         |
| Storage altitude                      | 0...50000 ft (0.00...15240.00 m) |

## Surge Protection and Filtering

|   |                  |
|---|------------------|
| NM Surge Response Time (ns)                 | 0 ns common mode |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 70 dB            |
| Surge energy rating                         | 3020 J           |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304249023 |
|------|--------------|

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | Db                     |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 2.36 in (6 cm)         |
| Package 1 Width              | 13.58 in (34.5 cm)     |
| Package 1 Length             | 7.56 in (19.2 cm)      |
| Package 1 Weight             | 2.98 lb(US) (1.35 kg)  |
| Number of Units in Package 2 | 6                      |
| Package 2 Height             | 15 in (381.00 mm)      |
| Package 2 Width              | 8 in (203.20 mm)       |
| Package 2 Length             | 15 in (381.00 mm)      |
| Package 2 Weight             | 19.58 lb(US) (8.88 kg) |
| SCC14                        | 10731304249020         |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product                            |
| REACH Regulation           | <a href="#">REACH Declaration</a>                |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>                              |

**Contractual warranty**

Warranty

Limited Lifetime

Recommended replacement(s)