

Product data sheet

Specifications



APC Performance SurgeArrest 12 Outlet with 2 Port 2.4 A USB Charger 120V

P12U2

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Height 12.24 in (31.1 cm)
Width 5.00 in (12.7 cm)
Depth 1.30 in (3.3 cm)
Net Weight 1.92 lb(US) (0.87 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Input Frequency 50/60 Hz
Switching current capacity 15 A

Output

Number of power socket outlets 12
Outlet standard NEMA 5-15R

Conformance

UL 1449 TVSS Rating L-N: 330
L-G: 400
N-G: 400

Product Certifications cULus

Standards FCC Part 15 class B

UL 1310
UL 1363
UL 1449

Equipment protection policy Lifetime : \$300000

Environmental

Ambient Air Temperature for Operation 32...113 °F (0...45 °C)

Relative Humidity 0...95 % non-condensing

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage Relative Humidity 0...95 % Non-condensing

Storage altitude 0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns) 1 ns common mode

EMI/RFI Noise rejection (100 kHz to 10 MHz) 75 dB

Peak current 56 kA common mode
196 kA normal mode

Surge energy rating 4320 J

Ordering and shipping details

GTIN 731304336563

Packing Units

Unit Type of Package 1 Db

Number of Units in Package 1 1

Package 1 Height 14.17 in (36 cm)

Package 1 Width 1.69 in (4.3 cm)

Package 1 Length 7.87 in (20 cm)

Package 1 Weight 2.16 lb(US) (0.98 kg)

Number of Units in Package 2 6

Package 2 Height 8.98 in (228.09 mm)

Package 2 Width 11.42 in (290.07 mm)

Package 2 Length 15.16 in (385.06 mm)

Package 2 Weight 14.4 lb(US) (6.53 kg)

Number of Units in Package 3 216

SCC14 10731304336560

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Mercury free Yes

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
----------	------------------

Recommended replacement(s)