

Product data sheet

Specifications



APC Performance SurgeArrest 8 Outlet 120V



P8

⚠ Discontinued on: 11 March 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V

Input Connection Type NEMA 5-15P

Cable length 6 ft (1.83 m)

Number of cables 1

Provided equipment User Manual

Physical

Color Black

Height 11.73 in (29.8 cm)

Width 2.99 in (7.6 cm)

Depth 1.10 in (2.8 cm)

Net Weight 1.37 lb(US) (0.62 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

Input

Input Frequency 50/60 Hz

Switching current capacity 15 A

Output

Number of power socket outlets 8

Outlet standard NEMA 5-15R

Conformance

UL 1449 TVSS Rating L-N: 330
L-G: 400
N-G: 400

Product Certifications	cULus
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$300000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	58 dB
Peak current	56 kA common mode 148 kA normal mode
Surge energy rating	3420 J

Ordering and shipping details

GTIN	731304336594
------	--------------

Packing Units

SCC14	10731304336591
-------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Lifetime
----------	----------

Recommended replacement(s)