TRIPP-LITE

AB Parallel Printer Cable (DB25 to Cen36 M/M), 6 ft. (1.83 m)

MODEL NUMBER: P606-006



Features

- Built to the IEEE 1284 standard to provide superior conductivity and support high-speed bi-directional printing
- Length: 6-ft. Connectors: DB25 male/Cent36 male
- Nickel plated connectors and gold plated copper contacts offer superior conductivity
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold

Specifications

OVERVIEW	
UPC Code	037332013521
Technology	Parallel
PHYSICAL	
Color	Black
Cable Jacket Color	Black
Cable Length (ft.)	6
Cable Length (m)	1.83

Highlights

- Superior molded cables with integral strain relief and foilshielding for maximum EMI/RFI protection
- Built to the IEEE 1284 standard to provide superior conductivity and support high-speed bi-directional printing.

System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Centronics 36 Female parallel port with high-speed Bi-Directional communication (although not essential).

Package Includes

 6-ft. AB Parallel Printer Cable DB25M to Cen36M

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

9.00 x 7.00 x 0.50	
22.86 x 17.78 x 1.27	
0.48	
0.22	
0.000 x 0.000 x 0.000	
CONNECTIONS	
DB25 (MALE)	
CENTRONICS 36 (MALE)	
STANDARDS & COMPLIANCE	
RoHS	
WARRANTY & SUPPORT	
Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.